

NX-TB38-MODUL-T1VR

NX-TB38-MODUL-2T1VR


NX-TB38-MODUL

Key features and benefits

- 1, 2 or 3 buttons available
- Easy integration with studs on the back
- 38 mm Industrial TrackBall - Dust and Water Proof
- Very robust metallic front plate (anthracite RAL 7021 color)
- PS/2 or USB interface
- Semi- or full customisation available
- Rugged construction, increased reliability
- COTS product

Specifications

Number of buttons :	1, 2 or 3, see ordering informations below
Dimensions :	99 x 136 x 25 mm (-MODUL version)
Protection level :	IP65 static (front area) IP54 dynamic (front area)
Ball diameter :	38 mm
Actuation force :	50 g
TrackBall Lifetime :	> 6 mil. revolutions
Mounting type:	Panel version (-MODUL)
Interface :	PS/2 or USB
Connectors :	Mini-DIN 6 pins or USB-A
Weight :	450g



Ordering informations

NX-TB38-MODUL-PS/2 :	38 mm TrackBall, PS/2 Interface, panel version, 3 mechanical buttons
NX-TB38-MODUL-USB :	38 mm TrackBall, USB Interface, panel version, 3 mechanical buttons
NX-TB38-MODUL-1T1VR-PS/2 :	38 mm TrackBall, PS/2 Interface, panel version, 1 stainless Steel button
NX-TB38-MODUL-2T1VR-USB :	38 mm TrackBall, USB Interface, panel version, 1 stainless Steel button
NX-TB38-MODUL-2T1VR-PS/2 :	38 mm TrackBall, PS/2 Interface, panel version, 2 stainless Steel buttons
NX-TB38-MODUL-2T1VR-USB :	38 mm TrackBall, USB Interface, panel version, 2 stainless Steel buttons

Semi or full customisation available