

L1855S-RT

Specification

Plastic case, 18.5" LCD monitor, 1366x768, 300nits



Features

- Foldable stand adds flexibility and comfort to your viewing preferences
- The extra-small footprint creates more work space on the desk
- Integrated amp and stereo speakers give you a complete multimedia experience
- 1366 x 768 pixels resolution provides sharp and brilliant images of text and graphics

Panel	Cell Type / Glass Surface	TFT LCD / Black Anti-Glare, low reflection coating		
	Aspect Ratio / Size	wide / 18.5" viewable diagonal area		
	Active Area / Pixel Pitch	409.8(H) x 203.4(V) mm / 0.3(H) x 0.3(V) mm		
	Native Resolution / Colors	1366(H) x 768(V) / 16.7 Million		
	Brightness / Contrast	300 cd/m ² (typ) / 1000 : 1		
	Response Time	≤ 5 ms		
	Viewing Angle (typical)	H. 170° (- 85° ~ + 85°) , V. 160°(- 80° ~ + 80°)		
	Light Source	CCFL , Long life, 50,000 hrs (typ)		
Input Sources	PC System	Signal	Analog RGB (0.7/1.0 V _{p-p} , 75 ohms)	
		Sync	Separate Sync, Composite Sync, Sync On Green	
		Frequency	F _h : 30 - 82Khz , F _v : 50 -75Hz	
	Audio System	2W speaker x 2		
Input Terminals	1 x VGA (15 Pin Female D-Sub) , 1 x PC Audio (Stereo Headphone Jack) , 1 x DC Jack			
Convenient Features	Auto Calibration , Back Light Adjustment , Plug&Play (VESA DDC/CI, DDC 2B)			
	OSD Multi-Languages , Wall Mount Ready (VESA 100 x 100 mm)			
Power	External AC-to-12VDC power adapter with universal / Auto-Sensing, AC 90 to 260V, 50 / 60 Hz			
Power Consumption	Operation / Power Saving	22 watt , < 1 watt (Support DPMS)		
Operating Condition	Temperature / Humidity	0°C ~ 50°C (32°F ~ 122°F) , 10% ~ 90% (no condensation)		
Storage Condition	Temperature / Humidity	- 20°C ~ 60°C (- 4°F ~ 140°F) , 10% ~ 90% (no condensation)		
Certification	FCC , CE			
Dimensions	Physical	With Base(W x H x D) : TBD		
		Without Base(W x H x D) : TBD		
	Carton	W x H x D = TBD		
Weight	N.W. / G.W.	5.0 Kgs / 6.0 Kgs		
Container Loaded	20ft / 40ft / 40ft HQ	TBD (Sets , By pallet)		

Options	Touch	Video / TV	Enhanced Panel	Others
	Resistive touch	DVI	Panel with LED backlight	Digital Signage(Stand alone)
	Protected glass	HDMI	Sun Light Readable	Motion Sensor
		SV + AV	Wide Temperature	Auto-Dimming Light Sensor



ZAC Pôle Actif - 4, allée du Piot
30660 Gallargues le Montueux
Tél.: 04 66 74 18 73