

# L2415S-RT

## Specification

Plastic case, 24" LCD monitor, 1920x1200, 400nits



### Features

- Foldable stand adds flexibility and comfort to your viewing preferences
- Integrated amp and stereo speakers give you a complete multimedia experience
- Enjoy crisp, clear, views of graphics and text from the 1000:1 contrast ratio, fast 5 ms response time, and resolutions up to 1920 x 1200

Panel	Cell Type / Glass Surface	TFT LCD / Black Anti-Glare, low reflection coating	
	Aspect Ratio / Size	Wide / 24" viewable diagonal area	
	Active Area / Pixel Pitch	546.4(H) x 352.0(V) mm / 0.27(H) x 0.27(V) mm	
	Native Resolution / Colors	1920(H) x 1200(V) / 16.7 Million	
	Brightness / Contrast	400 cd/m <sup>2</sup> (typ) / 1000 : 1	
	Response Time	≤ 6 ms (G-to-G)	
	Viewing Angle (typical)	H. 178° (- 89° ~ + 89°) , V. 178°(- 89° ~ + 89°)	
	Light Source	CCFL , Long life, 50,000 hrs (typ)	
Input Sources	PC System	Signal	Analog RGB (0.7/1.0 V <sub>p-p</sub> , 75 ohms)
		Sync	Separate Sync, Composite Sync, Sync On Green
		Frequency	F <sub>H</sub> : 30 - 82Khz , F <sub>V</sub> : 50 -75Hz
	Audio System	2W speaker x 2	
Input Terminals	1 x VGA (15 Pin Female D-Sub) , 1 x PC Audio (Stereo Headphone Jack) , 1 x DC Power Plug		
Convenient Features	Auto Calibration , Back Light Adjustment , Plug&Play (VESA DDC/CI, DDC 2B)		
	OSD Multi-Languages , Wall Mount Ready (VESA 100 x 100 mm)		
Power	External AC-to-12VDC power adapter with universal / Auto-Sensing, AC 90 to 260V, 50 / 60 Hz		
Power Consumption	Operation / Power Saving	75 watt , < 5 watt (Support DPMS)	
Operating Condition	Temperature / Humidity	0°C ~ 50°C (32°F ~ 122°F) , 10% ~ 90% (no condensation)	
Storage Condition	Temperature / Humidity	- 20°C ~ 60°C (- 4°F ~ 140°F) , 10% ~ 90% (no condensation)	
Certification	FCC , CE		
Dimensions	Physical	With Base(W x H x D) : TBD	
		Without Base(W x H x D) : TBD	
	Carton	W x H x D = 556 x 450 x 160 mm	
Weight	N.W. / G.W.	7.5 Kgs / 8.5 Kgs	
Container Loaded	20ft / 40ft / 40ft HQ	TBD (Sets , By pallet)	

Options	Enhanced Panel	Video / TV	Others
	Panel with LED backlight	DVI	Digital Signage(Stand alone)
	High brightness panel	HDMI	Motion Sensor
	Wide Temperature	SV + AV + TV	Light Sensor
	Sun Light Readable		Auto-Dimming



ZAC Pôle Actif - 4, allée du Piot  
30660 Gallargues le Montueux  
Tél.: 04 66 74 18 73