

# OF3205D

## Specification



### Features

- Modularize mechanical design provides flexible product configuration and easy maintenance
- Optional panel with ultra high brightness and super dynamic contrast, along option with auto-brightness sensor offers application in day and night
- Optional build-in PC eliminates need for separate media player to run content

|                     |  |   |   |
|---------------------|--|---|---|
| Panel               | Cell Type / Glass Surface  | TFT LCD / Black Anti-Glare, low reflection coating                          |   |
|                     | Aspect Ratio / Size  | Wide / 32" viewable diagonal area   |   |
|                     | Active Area / Pixel Pitch  | 697.69(H) x 392.26(V) mm / 0.51(H) x 0.51(V) mm                             |   |
|                     | Native Resolution / Colors   | 1366(H) x 768(V) / 16.7 Million   |   |
|                     | Brightness / Contrast  | 450 cd/m <sup>2</sup> (typ) / 2000 : 1                                      |   |
|                     | Response Time  | ≤ 6 ms (G-to-G)   |   |
|                     | Viewing Angle (typical)  | H. 178° (- 89° ~ + 89°) , V. 178°(- 89° ~ + 89°)                            |   |
|                     | Light Source   | CCFL , Long life, 50,000 hrs (typ)  |   |
|                     | Input Sources  | PC System   | Signal  |
| Sync                |  |   | Separate Sync, Composite Sync, Sync On Green            |
| Frequency           |  |   | F <sub>h</sub> : 30 - 82KHz , F <sub>v</sub> : 50 -75Hz |
| Audio System        |  | 3W Amplifier  |   |
| Input Terminals     | 1 x VGA (15 Pin Female D-Sub) , 1 x PC Audio (Stereo Headphone Jack) , 1 x DC Power Plug |   |   |
| Convenient Features | Auto Calibration , Back Light Adjustment , Plug&Play (VESA DDC/CI, DDC 2B)               |   |   |
|                     | OSD Multi-Languages , Wall Mount Ready (VESA 400 x 200 mm)                               |   |   |
| Power               | Internal power supply with universal / Auto-Sensing, AC 90 to 260V, 50 / 60 Hz           |   |   |
| Power Consumption   | Operation / Power Saving   | 130 watt , < 5 watt (Support DPMS)  |   |
| Operating Condition | Temperature / Humidity   | 0°C ~ 50°C (32°F ~ 122°F) , 10% ~ 90% (no condensation)                     |   |
| Storage Condition   | Temperature / Humidity   | - 20°C ~ 60°C (- 4°F ~ 140°F) , 10% ~ 90% (no condensation)                 |   |
| Certification       | FCC , CE   |   |   |
| Dimensions          | Physical   | With Flanges(W x H x D) : 780.0 x 492.0(Screw center-to-center) x 92.0 (mm) |   |
|                     |  | Without Flanges(W x H x D) : 780.0 x 472.0 x 92.0 (mm)                      |   |
|                     | Carton   | W x H x D = 895 x 605 x 225 mm  |   |
| Weight              | N.W. / G.W.  | 14.5 Kgs / 16.0 Kgs   |   |
| Container Loaded    | 20ft / 40ft / 40ft HQ  | TBD (Sets , By pallet)  |   |

| Options | Touch            | Video / TV           | Enhanced Panel           | Others                       |
|---------|------------------|----------------------|--------------------------|------------------------------|
|         | Resistive touch  | SV + AV              | Panel with LED backlight | Digital Signage(Stand alone) |
|         | Capacitive touch | SV + AV + AV_Looping | High brightness panel    | Networking Digital Signage   |
|         | SAW touch        | SV + AV + TV         | Wide Temperature         | Motion Sensor                |
|         | Infrared touch   |                      | Sunlight Readable        | Light Sensor                 |
|         | Protected glass  |                      |                          | Auto-Dimming                 |



ZAC Pôle Actif - 4, allée du Piot  
30660 Gallargues le Montueux  
Tél.: 04 66 74 18 73